



PRODUCT OVERVIEW

The T-Box Mk2 Cable Tester is designed to test electrical continuity and connection faults in balanced and unbalanced cables. Connector pairs are included for XLR, 1/4" jack, phono and 5 pin DIN (MIDI only). The phono connectors double-up as a simple continuity tester for checking fuses.

Simply plug in the cable to be tested and three tri-coloured LED's light green to show a correct polarity connection, red, and/or orange to show reverse connections and off to show an open or short to ground. A convenient diagnostic table on the underside of the T-Box shows LED colour combinations for any fault condition.

The T-Box is an invaluable tool for contractors, installation engineers, studios and equipment rental companies.

SPECIFICATIONS

ELECTRICAL

Power requirement: 2 x 9V Battery*

*suitable types include: PP3, MN1604 6LR6

Automatic shut off when test cable is disconnected

PHYSICAL

Connections: XLR 3 Pin
1/4" TRS jack
RCA /Phono
5 pin DIN **

** wired to pins 4 & 5 for MIDI cables

Temperature Range: Operating: 0°C to +50°C
Storage : -30°C to +75°C

Dimensions: 105 (4") W
125 (5") D
50 (2") H

Weight: 0.3kg Unit
0.36kg Shipping

DIMENSIONS

