

TCX20

Dual/Stereo Tube Compressor



PRODUCT OVERVIEW

The TCX20 is a dual channel Tube compressor, which can be linked for stereo processing. It features two active tube amp stages per channel; one stage at the input and one for the output Gain Make-Up. The input stage has a tube drive control with a 40dB range.

The compressor features variable Threshold and Ratio and variable rate Auto-Sensing Attack and Release. This form of semi-automatic circuitry gives fully variable control to the user, but backs it up with auto-sensing circuitry that makes the TCX20 both easy and forgiving to use.

Each channel is completed with an eight-segment LED bargraph, a 20dB output tube gain amplifier and a bypass button.

APPLICATIONS

As well as performing all the tasks of a professional compressor, the TCX20 also adds classic tube warmth to an instrument or final mix.

Use the TCX20 for:

- Increasing the power of a final mix
- Limiting PA signal levels
- Preventing distortion in recording
- Vocal levelling
- Fattening drums
- Emphasising solo instruments
- De-Essing and De-popping*

* using an equaliser with the sidechain insert.

SPECIFICATIONS

ELECTRICAL

Operating Levels:	-10dBV on TRS jack +4dBu on XLR
Frequency response:	±1dB, 20Hz to 20kHz
Noise:	<-87dBu
THD:	< 0.05%
Input impedance:	20k balanced
Max. input level:	+20dBu
Output impedance:	<100R ground sensing
Max. output level:	+20dBu
Compressor Threshold:	-30dB to +20dB
Ratio:	Variable 1:1 to 20:1
Gain adjustment:	±20dB
GR meter:	-2, -4, -6, -10, -15, -20dB
Attack & Release Variable window, Auto-Sensing	Attack: 0.1ms to 100ms Release: 40ms to 4s
Power Consumption:	7VA, 115/230VAC, 50/60Hz

PHYSICAL

Input connectors:	3 pin XLR, wired Pin 2 hot or TRS jack, wired Tip hot
Output connectors:	3 pin XLR, wired Pin 2 hot or TRS jack, wired Tip hot
Power Connection:	3 pin IEC socket. Detachable Lead
Dimensions:	483mm (19") W 200mm (8") D 44mm (1.75") H
Weight:	2.9kg
Shipping weight:	3.5kg



British
Originals





In keeping with our policy of continuous improvement LA Audio reserves the right to alter specifications without prior notice. Manufactured in the UK by LA Audio, 6-24 Southgate Road, London, N1 3JJ.

Tel: +44 (0)207 923 7447, FAX: +44 (0)207 241 3644. Web: www.laaudio.co.uk. email: sales@laaudio.co.uk

An SCV International Group Company

TCX20

Dual/Stereo Tube Compressor



British
Originals

In keeping with our policy of continuous improvement LA Audio reserves the right to alter specifications without prior notice. Manufactured in the UK by LA Audio, 6-24 Southgate Road, London, N1 3JJ.
Tel: +44 (0)207 923 7447, FAX: +44 (0)207 241 3644. Web: www.laaudio.co.uk. email: sales@laaudio.co.uk
An SCV International Group Company